

CITY OF HIGHLAND
Public Works Policies, Procedures and Standards

11.0 SIGNAGE

All signs shall be designed and installed in accordance with the latest edition of the California Manual on Uniform Traffic Control Devices and City of Highland Standards. See Section 12.0 for pavement marking materials.

1. All signs shall be placed on existing street sign posts or street light poles wherever possible.
2. Stop and warning signs shall have 3M Diamond Grade DG³ reflective sheeting with #1160 anti-graffiti film.
3. Other signs shall have 3M High Intensity Grade prismatic reflective sheeting with #1160 anti-graffiti film.
4. Stop signs shall be installed two (2) feet behind the face of curb at the BC of the curb return.
5. Limit lines shall be installed at all stop signs except if a crosswalk is installed. See City Standard Drawing No. 218 for limit line location.
6. A stop legend shall be installed in conjunction with a limit line when a street intersects a major highway or secondary highway. Stop legends shall also be installed at crosswalks. See City Standard Drawing No. 218 for stop legend location.
7. Sign posts shall be 2" x 2" x 10' without stop signs or 12' with stop signs mounted on the same post. Posts shall be installed into ground with 2-1/4" x 2-1/4" x 30" anchor, c.c.s.s. type. Attach post and anchor with two (2) drive rivets. There shall be a clearance of 7' between the finished grade and lower sign. Anchors shall extend no higher than 3" above finished grade.